

SALLI LIGHT



Light and affordable

Light and affordable with the two-part seat qualities. Single black polyurethane piece with a groove in the middle. Made in China, Finnish design.

SEAT

- Solid black polyurethane seat, groove in the middle.
- Models: Salli Light Basic, Salli Light Tilt (tilting), Salli Light Swing (swinging).
- Also available with a protective seat cover (wool or cotton)

TECHNICAL FEATURES

- Weight: Light Basic 6,1 kg, Light Swing 7 kg, Light Tilt 7.6 kg
- The chair must not be used or stored in temperatures lower than + 5 °C
- Warranty 5 years



GAS SPRINGS	User height (cm)	Chair height LIGHT BASIC (mm, min-max). with plastic base	Chair height LIGHT TILT (mm, min-max). with plastic base	Chair height LIGHT SWING (mm, min-max). with plastic base
Short	<150	465-595	485-610	525-655
Medium	150-175	540-720	550-740	590-780
Long	>165	630-875	640-890	690-930

Mini gas spring is available for special circumstances; use depends on the working height, not on the height of the user.

Note!

If you are using industrial or inline castors, the chair is 35 mm higher than the measurements shown in the table.

BASES



Plastic base

- Ø 580 mm
- Black



Aluminium base

- Ø 540 mm, aluminium
- Metallic or black

CASTORS



Soft standard

- Ø 65 mm
- For hard floors

Inline Industrial

- Ø 75 mm
- For uneven floors, ideal also for hairdressers and on wall-to-wall carpets

ACCESSORIES

Suitable For Salli Light

TOB & BOTTOM

Enables height adjustment without using the lever by hand. Recommended for hygienic environments, such as operating theatres and dental clinics. Ø 540 mm aluminium base required.



FOOT SUPPORT

A perfect accessory for high workstations to support the feet. Recommended for temporary use only. Ø 460 mm.

